



## SPECIFICATION

<b>Model NO.</b>	<b>CMSBHTC200FPE</b>	<b>CMSBTHC200FPE</b>
<b>Video Output Mode</b>	<b>AHD/TVI: 5M@20fps/12.5fps, 4M@30fps/25fps/15fps, 2M@30fps/25fps; CVI: 4M@30fps/25fps, 2M@30fps/25fps</b>	
<b>Camera</b>		
Image Sensor	1/3" CMOS Sensor	
Image Resolution	5M:2592*1944 4M:2560*1440 2M:1920*1080	
TV System	PAL/NTSC	
Electronic Shutter	Auto	
Minimum Illumination	Color : 0.03 lux@F2.0, AGC ON; B/W : 0 lux with IR	
Scanning System	Progressive Scan	
<b>Lens</b>		
Focus Length	3.6mm	
Focus Control	Fixed	
Lens Type	Fixed	
<b>Night Vision</b>		
IR Cut Filter	YES	
Infrared LED	42μ x 2PCS	
Infrared Distance	25M	
IR Status	AGC Auto Control	
<b>Camera Features</b>		
Starlight	N/A	
Day/Night	YES	
OSD Menu	YES	
WDR	DWDR	
UTC	YES	
Noise Reduction	DNR	
Coaxial Audio	YES(only TVI )	
White Balance	AUTO / MANUAL	
Gain Control	AUTO	
<b>General</b>		
Housing	Metal, IP67	
Bracket	NO	
Operation Temperature	-10°C ~ +60°C RH95% Max	
Storage Temperature	-20°C ~ +60°C RH95% Max	
Power Source	DC12V±10%, 500mA	
Dimension	∅ 96 x 91(H) mm	
Weight	600g	