

DS-PA201PS-16WB Control Panel



- Simple and elegant appearance design
- Wi-Fi, GPRS, 4G network for cloud communication
- Friendly app interface makes installation and use easier
- Up to 2000 m radio signal transmission range in open space

▪ Specification

Model		DS-PA201PS-16WB
Capacity	ARC	1
	Installer	1
	User	14
	Areas	4
	Wireless zones	16
	Wireless keypads	4
	Wireless sounders	4
	Wireless keyfobs	16
	Admin	1
	Logs	1000
Communication	Transmission technology	TRI-X 433.1-433.7 MHz
	Transmission range (free space)	up to 1,200 m
	Maximum effective radiated power (ERP)	25 mW max
	Radio signal modulation	2GFSK
	Encryption	AES-128
	Ethernet	1 8P8C socket
	Ethernet speed	≤10Mbps
	Wi-Fi	802.11 b/g/n
	Cellular	4G
	SIM slots	1
Notifications	APP notifications	Yes
	SMS notifications	Yes
	Calls notifications	Yes
	ARC notifications	Yes
	Event types	Alarms Faults

		System Events Operations
Software features	Upgrade OTA	Yes
	Protocol	SIA-DCS *SIA-DCS ADM-CID *ADM-CID OTAP Other proprietary protocols
Indication	Indication method	LED
Hardware features	Tamper-Proof	Yes
Electrical characteristics	Built-in backup battery	Yes
	Battery life	Up to 12 hours at normal temperature (The battery working time can be significantly reduced at low temperatures)
	Battery charging temperature	0 °C to +40 °C
General	Dimension (W×H×D)	165 x 165 x 37.5 mm
	Weight	410 g
	Operation temperature	-10 °C to +55 °C
	Operation humidity	10% to 90%
	Shell material	Plastic

▪ Available Model

DS-PA201PS-16WB/B-EU

DS-PA201PS-16WB/B-AU

DS-PA201PS-16WB/A-LA

DS-PA201PS-16WB/A-EU

- **Accessory**

- **Included**

DS-PC201N

LAN Module



Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
www.hikvision.com



Follow us on social media to get the latest product and solution information.



Hikvision



HikvisionHQ



HikvisionHQ



Hikvision_Global



Hikvision
Corporate Channel



hikvisionhq